

BIOFA (Colour Wax)

solvent free

Art. No. 2087

Properties

BIOFA Colorwachs protects and refines untreated wooden ceilings, cladding, planking, balconies, frames, shelves, furniture, etc. from soiling and abrasion. It consists of natural raw materials and contains no irritating or toxic additives. Suitable for surfaces not exposed to stress or exposed to minor stress. The treated surfaces are silk gloss, moisture-vapour permeable and dirt-repellent. The colour wax can be polished manually or mechanically after drying to increase the gloss level.

65 colour shades are available (see BIOFA Trox colour fan).

A topcoat of BIOFA Innengrundierung (Interior Primer) Art. No. 5005 increases the abrasion resistance, the wiping resistance and the gloss level of the finish. When using white colour wax, no topcoat of 5005 must be applied because the surface would turn yellow. Always carry out a preliminary test with 5005 on the respective colour wax.

Ingredients

Water, carnauba wax, pigments depending on colour shade, fatty acid alcohol ester, lavandin oil, bergamot oil (contains limes).

Instructions for use:

1. Pretreatment

Substrates must be dry (max. 12% moisture), absorptive, free of soiling, dust and grease. Appropriate sanding (at least P 180) is recommended.

2. Application

Stir well and apply evenly by brush, roller, spraying or wiping. Depending on the type of wood, colour and intensity may strongly deviate. Light-coloured areas in the wood absorb more colour (like negative stain). Work swiftly wet in wet on large areas to avoid

overlaps. Padding with a green pad while the material is still wet prevents roughening of the finish. After drying, polishing with a white pad is possible. If necessary, apply a 2nd coat and proceed as described above.

All colour shades can be mixed with each other as desired.

Attention! It is absolutely necessary to carry out a preliminary test! Do not dilute with water! Do not use under 12°C!

3. Cleaning of tools

Clean with water and BIOFA Brush Cleaner 0600 immediately after use.

Drying

A second coat can be applied after 20 to 30 minutes (20°C/50-55% rel. air humidity). The finish can be polished after 30-40 minutes.

Consumption/spreading rate per coat

23 - 32 ml/m² or 31 - 44 m²/l depending on the substrate's absorbency and nature.

Cleaning and maintenance

Wipe damp with a cloth, if necessary, clean with NACASA. Apply NAPLANA 2085 thinly with a cloth. NAPLANA 2085 provides additional protection and can be polished with a white pad. Another application of colour wax freshens the colour shade. **Carry out a preliminary test!**

Storage

Cool, above freezing point and sealed airtight. Use up opened containers soon. Minimum shelf life of unopened containers: 1 year!

Container size

1 l / 5 l / 20 l PE or PP containers.

The data and information provided in this technical data sheet are binding. If it is necessary to deviate from these provisions, the Application Technology Department of BIOFA must be consulted in advance. The general rules for structural engineering are to be complied with. With publication of this technical data sheet all previous data sheets regarding this product are no longer valid.

Disposal

Take residual amounts of liquid product to collection sites for used paint/lacquer or dispose of them in compliance with any and all local regulations. Small residual amounts and soaked working materials can be disposed of with the household garbage after they dry.

Only turn in packages that are clean or free of residues or have hardened adhesions for recycling or disposal according to local regulations! Packages that cannot be cleaned or emptied properly are to be treated and disposed of like the product itself!

Safety instructions

Keep out of reach of children. In case of eye contact, thoroughly rinse with water immediately

VOC identification according to Deco-paint Directive and ChemVOCFarbV (Directive on the limitation of emissions of volatile organic compounds due to the use of organic solvents in paints and varnishes):

EU limit value (cat. A/f): 130 g/l (2010)

2087 contains at most 1 g/l VOC.

Waste Incineration Ordinance[AVV]-
Waste Code according to European Waste Catalogue: 08 01 12

The data and information provided in this technical data sheet are binding. If it is necessary to deviate from these provisions, the Application Technology Department of BIOFA must be consulted in advance. The general rules for structural engineering are to be complied with. With publication of this technical data sheet all previous data sheets regarding this product are no longer valid.