

BIOFA Farbstabilisator (Colour Stabiliser) transparent Art. No. 2108

Properties

BIOFA Farbstabilisator is a transparent stabiliser based on natural ingredients. It is suitable for all BIOFA oil systems on light-coloured substrates.

Thanks to this additive, light-coloured surfaces virtually keep their natural character. The natural darkening and discolouring is reduced.

Ingredients

Aliphatic hydrocarbons, titanium dioxide, succinic acid ester, swelling clay.

Application

Stir BIOFA Farbstabilisator thoroughly, and up to 5% percentage weight (with stone oil up to 10%) into the specific BIOFA-oil then mix until homogenous prior to use. **Stir the oil occasionally. Always carry out a preliminary test.**

Attention! Provide optimum fresh air circulation during product application and drying!

Cleaning of tools

Clean with BIOFA Verdünnung (Thinner) 0500 immediately after use.

Storage

Cool, dry and sealed airtight.

Container size

0.375 l metal containers.

Safety instructions

Repeated contact can cause rough, cracked skin. Keep out of reach of children. Do not inhale vapour/aerosol. Only use in well-ventilated areas. Wear adequate skin protection when using!

Attention! Store work materials such as rags, sponges, clothes, sanding dust, etc. soaked with oil in airtight metal containers or rinse, spread and allow to dry on non-inflammable surface (**risk of spontaneous ignition!**).

Disposal

Dispose of liquid product residue at collection points for old paints/varnishes or dispose of according to locally applicable regulations. Small quantities of residue and soaked work materials can be disposed of along with domestic waste after drying.

Only recycle cleaned or completely empty packaging with cured deposits or dispose of according to locally applicable legal regulations. Uncleanable packaging and packaging not emptied appropriately must be treated and disposed of like the product!

Waste Incineration Ordinance[AVV]-
Waste Code according to European Waste
Catalogue: 08 01 11*

The data and information provided in this technical data sheet are binding. If it is necessary to deviate from these provisions, the Application Technology Department of BIOFA must be consulted in advance. The general rules for structural engineering are to be complied with. With publication of this technical data sheet all previous data sheets regarding this product are no longer valid.